



KEY

Cone

Sign

Work area

Traffic light head

Traffic light phase

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.

Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.

Dual carriageway National speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).

2) 45 degree tapers have 1.5m spacing and no relaxations.

3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones, Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Project:			
Queens Rd			
GL10 2QG			
Title:			
Full Road Closure			
DTM/LC			
1			

SAFER ROADWORKS

Design:

SRW

Drawn:

LC

Chkd:

TS

Date:

29/04/25

Status:

A3 - NTS

Proposed

Drawing No

DTM/LC

Rev:

1

XE|IAD

Revisions

Rev	Description	By	Chk	Date

Client:

Min width of sidewalks safety zone (S)

0.5 m

Min length of longways clearance (L)

0.5 m

Speed of the road

30